

## LIST OF CONTENTS

<b>CHAPTER- I INTRODUCTION</b>		<b>1-7</b>
1.1	Preamble	1
1.2	General Overview	1
1.3	Motion Caused by Earthquakes	3
	1.3.1 Features of Earthquakes	3
	1.3.2 Concept of Resonance	4
	1.3.3 RS - Response Spectrum	5
1.4	Structure Reaction	5
	1.4.1 Consequence of Surface Acceleration	5
	1.4.2 Effects of Stiffness and Ductility	6
	1.4.3 Damping's Impacts	6
1.5	Thesis Organization	6
<b>CHAPTER- II COMPONENTS OF BASE ISOLATION SYSTEM</b>		<b>8-15</b>
2.1	Preamble	8
2.2	Parts of Base Isolation Systems	8
2.3	Elastometric Bearing	8
	2.3.1 Natural Rubber Bearing (NRB)	8
	2.3.2 Lead Rubber Bearing (LRB)	10
	2.3.3 High Damping Natural Rubber Bearing (HDRB)	11
2.4	Moving Mechanisms	11
	2.4.1 Natural Friction Bearing	11
	2.4.2 Cable Friction Bearing	12
	2.4.3 Resilient Friction Base Isolators	13
	2.4.4 Friction Pendulum Bearing	14
2.5	Limiting Devices	15

<b>CHAPTER- III LITERATURE REVIEW OF BASE ISOLATION SYSTEM</b>		<b>16-29</b>
3.1	Preamble	16
3.2	Literature Survey	16
3.3	Observations from Literature Survey	28
3.4	Summary	29
<b>CHAPTER- IV METHODOLOGY OF RESEARCH</b>		<b>30-55</b>
4.1	Preamble	30
4.2	Scope of Work	30
4.3	Objectives of the Study	31
4.4	Hypothesis	32
4.5	Sample Model	32
	4.5.1 G+12 Storey Model Details	32
	4.5.2 G+22 Storey Model Details	35
4.6	Sample Model Case	38
	4.6.1 Case (a) G+12 Storey Reinforced Concrete (RC) Structure	38
	4.6.2 Case (b) G+22 Storey Reinforced Concrete (RC) Structure	39
4.7	Important Design Factors	39
	4.7.1 Loads	39
	4.7.2 Analytical Procedures	39
	4.7.3 Design Philosophies	40
	4.7.4 Building Components Design	41
4.8	Design Calculation for R.C.C.	42
	4.8.1 Analysis Method	42
4.9	Research Methodology	54
4.10	Summary	55

<b>CHAPTER- V DESIGN OF BASE ISOLATION BEARING</b>		<b>56-164</b>
5.1	Preamble	56
5.2	Design of LRB for G+12 Storey RC Structure.	56
	5.2.1 LRB for Biaxial Load - 1638 KN	56
	5.2.2 LRB for Uniaxial Load - 2487 KN	64
	5.2.3 LRB for Axial Load - 3920 KN	72
5.3	Design of Triple Friction Pendulum Bearing (TFPB) for G+12 Storey RC Structure.	80
	5.3.1 TFPB for Biaxial Load - 1638 KN	80
	5.3.2 TFPB for Uniaxial Load - 2487 KN	90
	5.3.3 TFPB for Axial Load - 3920 KN	100
5.4	Design of Lead Rubber Bearing (LRB) for G+22 Storey RC Structure.	110
	5.4.1 LRB for Biaxial Load - 3342 KN	110
	5.4.2 LRB for Uniaxial Load - 4627 KN	118
	5.4.3 LRB for Axial Load - 6860 KN	126
5.5	Design of Triple Friction Pendulum Bearing (TFPB) for G+22 Storey RC Structure.	134
	5.5.1 TFPB for Biaxial Load - 3342 KN	134
	5.5.2 TFPB for Uniaxial Load - 4627 KN	144
	5.5.3 TFPB for Axial Load - 6860 KN	154
5.6	Summary	164
<b>CHAPTER- VI ANALYSIS OF RESULTS</b>		<b>165-197</b>
6.1	Preamble	165
6.2	Result Comparison for Case (a) G+12 Storey Reinforced Concrete (RC) Structure. (Case-I with Case-II).	165
	6.2.1 Time Period.	165
	6.2.2 Base Shear.	166

	6.2.3 Storey-Displacement.	167
	6.2.4 Storey-Drift.	169
	6.2.5 Steel Reduction.	171
	6.2.6 Overall Cost Economy.	172
6.3	Result Comparison for Case (a) G+12 Storey Reinforced Concrete (RC) Structure. (Case-I with Case-III).	173
	6.3.1 Time Period.	173
	6.3.2 Base Shear.	174
	6.3.3 Storey-Displacement.	175
	6.3.4 Storey-Drift.	177
	6.3.5 Steel Reduction.	179
	6.3.6 Overall Cost Economy.	180
6.4	Result Comparison for Case (b) G+22 Storey Reinforced Concrete (RC) Structure. (Case-IV with Case-V).	181
	6.4.1 Time Period.	181
	6.4.2 Base Shear.	182
	6.4.3 Storey-Displacement.	183
	6.4.4 Storey-Drift.	185
	6.4.5 Steel Reduction.	187
	6.4.6 Overall Cost Economy.	188
6.5	Result Comparison for Case (a) G+22 Storey Reinforced Concrete (RC) Structure. (Case-IV with Case-VI).	189
	6.5.1 Time Period.	189
	6.5.2 Base Shear.	190
	6.5.3 Storey-Displacement.	191
	6.5.4 Storey-Drift.	193
	6.5.5 Steel Reduction.	195

	6.5.6 Overall Cost Economy.	196
6.6	Summary	197
<b>CHAPTER- VII CONCLUSIONS</b>		<b>198-199</b>
7.1	Future Work	199
<b>BIBLIOGRAPHY</b>		<b>200-206</b>
<b>PUBLICATIONS</b>		
<b>CERTIFICATE</b>		
<b>PLAGIARISM REPORT</b>		